# DIVISION 15 MECHANICAL

### 15300 SMOKE ALARMS

### PART 1 - GENERAL

#### 1.1 WORK

- A. Provide and install smoke alarms as listed on the **Scope**, per the building code and as specified herein.
- B. Provide and install smoke alarms that are listed and labeled by an independent testing agency.

#### 1.2 SUBMITTALS

A. Supply **Owner** with smoke alarm manufacturer's operating instructions.

### PART 2 - MATERIALS AND PRODUCTS

### 2.1 MATERIALS

- A. Smoke alarms shall be listed and labeled by an independent testing agency.
- B. Smoke alarms shall be equipped with a "hush button" if the alarm is located within 20 feet of the main cooking appliance within the dwelling unit.

#### PART 3 - EXECUTION

### 3.1 LOCATIONS

- A. Smoke detectors shall be installed in locations per the building code and as specified herein:
  - On floor levels that contain one or more sleeping areas, an alarm shall be installed outside the sleeping rooms, in the vicinity of each sleeping area.
  - An alarm equipped with a "hush button" is required if the smoke detector is installed within 20 feet of the main cooking appliance within the dwelling unit.
  - On floors that do not contain sleeping areas, an alarm shall be installed in a common area on each floor level
  - An alarm shall be installed in the basement in the vicinity of the basement stairway.
  - An alarm shall be installed at the top of common stairways in a duplex.
  - Alarms need not be installed in attics or storage areas.

## 3.2 INSTALLATION

- A. Smoke alarms shall be installed as soon as possible after the start of work, preferably prior to the start of work at the property.
- B. Install smoke alarms per manufacturer's instructions and as specified herein:
  - Install smoke alarms on ceilings at least 6 inches away from walls.
  - Install smoke alarms on walls within 12 inches but not less than 6 inches away from ceiling.
  - On vaulted ceilings, install smoke alarm at highest point of ceiling.
  - Do not install smoke alarms in kitchens or bathrooms.

# 3.3 INSPECTION

- A. Smoke alarms may be tested for proper operation.
  - Defective smoke alarms shall be replaced.
  - Batteries shall be replaced in all existing operational smoke alarms throughout building.